

TUBE-LUBE® 326

35000 SERIES



THE PRODUCT

Well tried and tested and in abundant use across Europe for many years, this one lubricant is what you need for all your cable pulling requirements.

Demand for this product is steadily growing mostly due to the many benefits it offers which include:

- Excellent lubrication and reduction of friction – field tests show pulling loads can be reduced by over 50% - on par with the other leading brands
- Proven to reduce the coefficient of friction – tests on PVC duct with polyethylene jacketed cable show this to be 0.13
- Lower friction means longer cable pulls. Lower viscosity means less drag on the jacket
- Clean and easy to use – spray what you need where it's needed for less waste
- Lubricant will flow around the cable when sprayed on, simply leaving a 5 mil coating of lubricant all around the cable jacket eliminating dry spots on the cable and further reducing friction. This also reduces usage by up to 50%
- Can be used equally well for heavy power cable or CATV cable
- Suitable for cable blowing. In Europe it is recommended by Lancier, one of the original developers of cable blowing machines and equipment
- Can be used with several different applicator systems now offered
- Good for winter or summer temperatures (-4°F to 149°F / -20°C to 65°C)
- Minimal evaporation – active ingredients do not dry out after application so cable removal years later is easy. Unfinished applications one day can easily be started up again the next day
- Non-flammable
- Contains no silicone oils, yet is compatible with silicone
- Contains no VOC's (Volatile Organic Compounds)
- Safe, non-toxic and biodegradable
- Successfully tested to IEEE standards for determining compatibility of pulling lubricants, including Low-Smoke Zero-Halogen (LSZH) jacket and Semi-Conductive materials.
- Successfully tested to ASTM standards for environmental stress cracking of cable jackets, also including Low-Smoke Zero-Halogen (LSZH) jacket
- Price competitive on a gallon to gallon basis alone – now figure in the much lower usage and there are excellent savings to be gained

THE PACKAGING

TUBE-LUBE® 326 is available in many different forms including:

- 1 quart spray bottle for smaller premise type applications, sold only as a 12 pack
- 4 pack of 1 gallon jugs (available in pallets of 44 packs) for larger users who prefer the 1 gallon jugs, (Extra 10% discount on pallet loads)
- Stackable 5 gallon container (available in pallets of 36 containers) for larger users who prefer the 5 gallon containers, (Extra 10% discount on pallet loads)
- In large 265 gallon totes, for the very large user who prefers to put the tote on the dock and let the crews fill up as needed. These totes have a spout and shut off valve located at the bottom of the tote and are returnable and can be re-filled, therefore saving even more costs

Part No.	Description	Weight
35000-002	1 QUART SPRAY BOTTLE - 12 PACK	26.76 LB
35000-410	1 GALLON JUG - 4 PACK	36.0 LB
35000-050	5 GALLON CONTAINER	38.0 LB
35000-055	55 GALLON BARREL	485 LB
35000-265	265 GALLON TOTE C/W SPOUT AND SHUT-OFF	2500 LB



MSDS Sheet Available on our Website

CABLE PULLING LUBRICANTS



Toll Free: 1-800-WCT-PROD (928-7763) Web Site: www.wctproducts.com
Tel: 310-822-5212
Fax: 310-306-9343
E-mail: info@wctproducts.com