

Duct Entry Guide

The Duct Entry Guide is unique for two reasons. First, it has an extra long tube section that goes inside the duct (see dimension A in the diagram on the right) for greater stability.

Second, because of the built-in spray nozzle for the DCD Tube-Lube® 326 application, there is one half of a quick-disconnect coupling attached to a spray nozzle that will direct the lubricant right onto the cable as it is fed into the ducting. This is a unique feature for a unique lubricant.



Part No.	Spare Sheave	3:1 Safe Working Load	Duct Diameter	A	Weight
32500-125*	32900-202P**	3,000 lb	1-1/4"	7-1/2"	7.4 lb
32500-150*	32900-202P**	3,000 lb	1-1/2"	7-1/2"	7.5 lb
32501-125*	32900-202P**	3,000 lb	Extension Quadrant	-	5.7 lb
32500-200	32900-303	3,000 lb	2"	7-1/2"	5.3 lb
32500-250	32900-303	3,000 lb	2-1/2"	7-1/2"	5.7 lb
32500-300	32900-307	6,000 lb	3"	9-1/2"	14.1 lb
32500-400	32900-407	6,000 lb	4"	11-1/2"	19.0 lb
32500-480	32900-407	6,000 lb	4" Schedule 80	11-1/2"	17.0 lb
32500-500	32900-507	6,000 lb	5"	13-1/2"	24.0 lb
32500-600	32900-611	6,000 lb	6"	15-1/2"	44.0 lb

* For use with Fiber Optic Cable only. Extension Quadrant may be used with -125 & -150 only.

** The 'P' style of Sheave is made from industrial grade plastic.



Part No.	Description	Weight
35000-001	1 Quart Spray Bottle - Single	2 lb
35000-002	1 Quart Spray Bottle - 12 pack	27 lb
35000-410	1 Gallon Jug - 4 pack	36 lb
35000-050	5 Gallon Container	38 lb
35000-265	265 Gallon Tote (comes with spout and shut-off)	2,500 lb