


Corner Guides

DCD Corner Guides are designed to withstand a 10,000 lb working line load with a 3:1 safety factor. The sheaves run in high strength iron-bronze bushings. The Corner Guides also have a wide base for stability, a deep lip for hooking into the manhole and two locations for hold down bars and lightening holes added everywhere possible.






Guide Part No.	Sheave Only	Sheave Width	Sheave Diameter	Weight
32300-400	32900-411	4"	11"	58.5 lb
32300-500	32900-511	5"	11"	63.5 lb
32300-600	32900-611	6"	11"	70.5 lb
32300-800	32900-811	8"	11"	88.5 lb

Note: Add 'F' to end of part number for Flat Bottom Sheave.

Wire Rope Guide

DCD Wire Rope Guides are designed to withstand over 10,000 lb safe working line load. The hardened rollers run on ball bearings at each end for smooth easy rotation and the rollers have a flange at each end to prevent the rope from riding off either side. The product also has an extra deep lip to hook into the manhole.






Spare		3:1 Safe	Sheave	Sheave	Weight
Part No. Sheave		Working Load	Width	Diameter	
32400-200	32900-702	10,000 lb	7"	2"	28.0 lb

Rim Roller

This product is designed to fit over the rim surrounding many electrical installations. While cable is being installed, this product will allow the cable to run over that rim without tearing or damaging the jacket.





Part No.	Spare Sheave	3:1 Safe Working Load	Sheave Width	Sheave Diameter	Weight
32450-400	32900-407	10,000 lb	4"	7"	14.5 lb