

VM-Clamp

Specifications	VM-Clamp	VX2/50 Clamp	VX4/100 Clamp	VX5/125 Clamp	VX18/450F Clamp (Flexible Clamp)
Description		2in (50mm) clamp	4in (100mm) clamp	5in (125mm) clamp	18in (450mm) flexible clamp
Maximum Cable/Pipe Diameter		2in (50mm)	4in (100mm)	5in (125mm)	18in (450mm)
Weight		4m – 1.26lbs (0.57kg) 7m – 1.59lbs (0.72kg)	4m- 1.67lbs (0.76kg) 7m- 2.07lbs (0.94kg)	4m - 1.76lbs (0.80kg) 7m – 2.11lbs (0.96kg)	1.32lbs (0.74kg)
Dimension (exclude cable)		7.5in(L) x 4.4in(W) x 1.3in(H) (190mm x 113mm x 33mm)	9.3in(L) x 5.8in(W) x 1.3in(H) (235mm x 147mm x 33mm)	10.6in(L) x 6.7in(W) x 1.6in(H) (270mm x 170mm x 40mm)	18in(D) x 1.22in(H) (457.2mm x 31mm)
Cable Length		13ft (4m) and 23ft (7m)			15ft (5m), length of clamp 4.8ft (1.45m)
Compatible with Transmitters		Loc-1Tx, Loc-5Tx, Loc-10Tx, VM-550 Tx, VM-810 Tx, VM-850 Tx			Loc-1Tx, Loc-5Tx, Loc-10Tx
Approvals		CE/FCC			
Frequency Range		Any frequency between 8.19 kHz and 83.1 kHz			Any frequency between 33 kHz and 82 kHz
Temperature Range		Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)			
Weatherproof		IP65			
Shipping Weight		4m – 1.96lbs (0.89kg) 7m – 2.29lbs (1.04kg)	4m – 2.18lbs (0.99kg) 7m - 2.56lbs (1.16kg)	4m – 2.27lbs (1.03kg) 7m - 2.62lbs (1.19kg)	2.34lb (1.06kg)
Shipping Dimension		13in(L) x 11.3in(W) x 3.3in(H) (330mm x 287mm x 85mm)			
Warranty		12 months			

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.



Toll-Free: 800-WCT-PROD (928-7763)
Local Phone: 310-822-5212
Fax: 310-306-9343
Email: info@wctproducts.com
Address: 13309 Beach Ave.
 Marina del Rey, CA 90292
Website: www.wctproducts.com