

A. Typical Applications

Item	Parameter
Description	LPC Separation Filter
Uses	To apply the transmitter signal to cables carrying up to 240V AC

B. LPC Separation Filter Assembly

Item	Parameter
Construction	High impact ABS
Weight	0.8lbs (0.36kg)
Dimension	7.5in(L) x 2.8in(W) x 2.4in(H) (190mm x 72mm x 62(H) mm)
Power Supply Options	Transmitter provides power in, the output leads from the separation filter can be connected to conductors carrying up to 240V AC
External Connectors	1 x XLR 3 pin plug

C. Operational

Item	Parameter
Controls	Rotary knob – phase switching
Frequency Range	From 50 Hz to 200kHz
Compatible With Transmitter	Loc10Tx, Loc5Tx, Loc-1Tx

D. Environmental

Item	Parameter
Temperature Range	Operating : -4°F to 122°F (-20°C to 50°C) Storage : -40°F to 140°F (-40°C to 60°C)

E. Warranty

Item	Parameter
Warranty	12 months

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.



Toll-Free: 800-WCT-PROD (928-7763)
 Local Phone: 310-822-5212
 Fax: 310-306-9343
 Email: info@wctproducts.com
 Address: 13309 Beach Ave.
 Marina del Rey, CA 90292
 Website: www.wctproducts.com