




## Power-Grip™ (Lug)

The Power-Grip™ pulling eye is reusable and has a lug style head that will attach directly to a swivel. All materials are stainless steel. Only four body sizes are used to cover the range from 1/0 to 5000 MCM cable. Note that these pulling eyes should always be used with a Line Swivel (00505 series).



Part No.	Maximum Cable Size	Maximum Core Diameter	Power-Grip Components					Weight	Threaded Cone Nut	Tapered Insert	Body	Fits Line Swivels
			A	B	C	D						
24000-001	1/0 AWG	0.39" 9.9 mm	1-1/4" 32 mm	11/32" 8.7 mm	1/2" 13 mm	3-7/8" 98 mm	0.68 lb 0.30 kg	24006-001	24005-001	24007-001	00505-010 to 00505-027	
24000-002	2/0 AWG	0.44" 11.1 mm	1-1/4" 32 mm	11/32" 8.7 mm	1/2" 13 mm	3-7/8" 98 mm	0.67 lb 0.30 kg	24006-002	24005-001	24007-001		
24000-003	3/0 AWG	0.50" 12.7 mm	1-1/4" 32 mm	11/32" 8.7 mm	1/2" 13 mm	3-7/8" 98 mm	0.64 lb 0.29 kg	24006-003	24005-001	24007-001		
24000-004	4/0 AWG	0.54" 13.7 mm	1-1/4" 32 mm	11/32" 8.7 mm	1/2" 13 mm	3-7/8" 98 mm	0.61 lb 0.27 kg	24006-004	24005-001	24007-001		
24000-025	250 MCM	0.61" 15.5 mm	1-1/4" 32 mm	11/32" 8.7 mm	1/2" 13 mm	3-7/8" 98 mm	0.58 lb 0.26 kg	24006-025	24005-001	24007-001	00505-015 to 00505-030	
24000-030	300 MCM	0.62" 15.7 mm	1-1/4" 32 mm	11/32" 8.7 mm	1/2" 13 mm	3-7/8" 98 mm	0.57 lb 0.26 kg	24006-030	24005-001	24007-001		
24000-035C	350 MCM Compact	0.65" 16.5 mm	1-7/8" 48 mm	3/8" 9.5 mm	5/8" 15.9 mm	4-3/4" 120 mm	1.88 lb 0.85 kg	24006-035C	24005-035	24007-035		
24000-035	350 MCM	0.71" 18.0 mm	1-7/8" 48 mm	3/8" 9.5 mm	5/8" 15.9 mm	4-3/4" 120 mm	1.84 lb 0.83 kg	24006-035	24005-035	24007-035		
24000-050	500 MCM	0.81" 20.6 mm	1-7/8" 48 mm	3/8" 9.5 mm	5/8" 15.9 mm	4-3/4" 120 mm	1.75 lb 0.79 kg	24006-050	24005-035	24007-035	00505-020 to 00505-035	
24000-060	600 MCM	0.91" 23.1 mm	1-7/8" 48 mm	3/8" 9.5 mm	5/8" 15.9 mm	4-3/4" 120 mm	1.73 lb 0.79 kg	24006-060	24005-035	24007-035		
24000-070	700 MCM	0.97" 24.6 mm	2-1/8" 54 mm	1/2" 13 mm	13/16" 20.5 mm	5-5/8" 142 mm	2.55 lb 1.15 kg	24006-070	24005-070	24007-070		
24000-075C	750 MCM Compact	0.94" 23.8 mm	2-1/8" 54 mm	1/2" 13 mm	13/16" 20.5 mm	5-5/8" 142 mm	2.51 lb 1.14 kg	24006-075C	24005-070	24007-070		
24000-075	750 MCM	1.00" 25.4 mm	2-1/8" 54 mm	1/2" 13 mm	13/16" 20.5 mm	5-5/8" 142 mm	2.47 lb 1.12 kg	24006-075	24005-070	24007-070	00505-035 to 00505-041	
24000-100C	500 mm <sup>2</sup> Compact	1.03" 26.2 mm	2-1/8" 54 mm	1/2" 13 mm	13/16" 20.5 mm	5-5/8" 142 mm	2.40 lb 1.09 kg	24006-100C	24005-070	24007-070		
24000-100	1000 MCM	1.15" 29.2 mm	2-1/8" 54 mm	1/2" 13 mm	13/16" 20.5 mm	5-5/8" 142 mm	2.30 lb 1.04 kg	24006-100	24005-070	24007-070		
*24000-125	1250 MCM	1.29" 32.8 mm	2-3/4" 70 mm	3/4" 19 mm	1-1/32" 26 mm	7-15/16" 202 mm	6.37 lb 2.88 kg	24006-125	24005-125	24007-125		
*24000-150	1500 MCM	1.41" 35.8 mm	2-3/4" 70 mm	3/4" 19 mm	1-1/32" 26 mm	7-15/16" 202 mm	6.13 lb 2.78 kg	24006-150	24005-125	24007-125	00505-035 to 00505-041	
*24000-175	1750 MCM	1.53" 38.9 mm	2-3/4" 70 mm	3/4" 19 mm	1-1/32" 26 mm	7-15/16" 202 mm	5.84 lb 2.64 kg	24006-175	24005-125	24007-125		
*24000-200	2000 MCM	1.63" 41.4 mm	2-3/4" 70 mm	3/4" 19 mm	1-1/32" 26 mm	7-15/16" 202 mm	5.53 lb 2.50 kg	24006-200	24005-125	24007-125		
*24000-200C	45 mm 2500 MCM	1.75" 44.5 mm	2-3/4" 70 mm	3/4" 19 mm	1-1/32" 26 mm	7-15/16" 202 mm	5.40 lb 2.45 kg	24006-200C	24005-125	24007-125		
*24000-300	3000 MCM	1.85" 47.0 mm	2-3/4" 70 mm	3/4" 19 mm	1-1/32" 26 mm	6-25/32" 172 mm	4.64 lb 2.11 kg	24006-300	24005-125	24007-125	00505-045 & 00505-050	
*24000-300C	1800 mm <sup>2</sup>	2.06" 52.4 mm	4-1/2" 114 mm	1" 25 mm	1-3/4" 44.5 mm	11-11/16" 297 mm	25.8 lb 11.7 kg	24006-300C	24005-500	24007-500		
*24000-500	5000 MCM	2.52" 64.0 mm	4-1/2" 114 mm	1" 25 mm	1-3/4" 44.5 mm	11-11/16" 297 mm	23.7 lb 10.8 kg	24006-500	24005-500	24007-500		

Note: Additional sizes are available upon request. Please contact Customer Service for more information.

\* Larger Power-Grips are machined from alloy steel and plated.