



SPECIFICATIONS

Product Description: **VENTILATION BLOWER, STANDARD**
Part Number: **9530**
Style: **AXIAL FAN 26" (66.04cm)**

GENERAL DESCRIPTION:

Allegro's 26" (66.04cm) blower offers a high powered motor for applications requiring a maximum amount of output. It offers the highest output of any of our blowers.

CONSTRUCTION:

- Complete unit epoxy powder coated in "safety orange"
- Interchangeable flange for intake/exhaust side mounting
- 16 gauge cold rolled steel housing
- 3/16" (.476cm) motor base
- Bolted motor mount construction
- Integrated carrying handles on four sides
- Steel/zinc plated grill
- Equipped with four rubber feet



MOTOR:

HP: 2 HP, Single Phase, thermally protected
Volts: 115/230V AC, 60 Hz
Max RPM: 1725
Cord: 12' (3.66m) 12/3 AWG, SJOOW Neoprene 300V medium duty
Plug: NEMA 5-30P or NEMA 6-30P (Twist Lock type)

FAN:

- Glass reinforced polypropylene (PPG) three blade fan with aluminum hub
- Moving fan mounted 1 5/8" (4.12cm) from grill for safety, grill gap-5/16" (0.79cm)

DUCTING: (Optional)

- Retractable, non-collapsible design
- Single-ply, PVC coated, vinyl and polyester materials, temperature resistant up to 180°F (82.2°C)
- Yellow color with black weather-strip and integrated nylon straps
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

BLOWER DIMENSIONS:

Length In. (cm)	Width In. (cm)	Height In. (cm)	Weight Lbs. (Kg)
19" (48.3 cm)	28" (71.1 cm)	28 ½" (72.4cm)	105 lbs (47.6 kg)

FLOW RATES: (CFM calculated using 15' (4.75cm) of 26" (66.04cm) ducting)

Free Air CFM (m ³ /hr)	One 90° Bend CFM (m ³ /hr)	Two 90° Bends CFM (m ³ /hr)
9570 (16,259.52)	8610 (14,628.47)	7750 (13,167.33)