



# DUCT HUNTER™ TRACEABLE RODDERS

Less Disruption To Roads & Landscapes  
Minimal Pavement Breakage, Excavation & Restoration



The Duct Hunter™ is a continuous fiberglass duct rodder with a copper wire embedded in the rod core. Connecting a signal transmitter to the rod energizes the wire, allowing the user to trace the continuous path of the pipe with a receiver. Works with any non-conductive pipe, such as PE, PVC, concrete, clay or tile. One person can do the job with minimal or no excavation.

Copper Wire Embedded In Fiberglass Rod Core With Red Polymer Jacket



	Mini Duct Hunter™	Mini Duct Hunter™	Duct Hunter™	Duct Hunter™	Duct Hunter™	Duct Hunter™
Applications	<ul style="list-style-type: none"> <li>Trace Fiber Optic Micro-Duct</li> <li>Trace Sewer Laterals &amp; Septic Lines; Fiberglass Will Not Rust</li> </ul>		<ul style="list-style-type: none"> <li>Trace To Depths Up To 10'</li> <li>Trace Sewer Laterals To Confirm No Cross Bore Has Occurred</li> <li>Trace Ductile Iron, Plastic, Tile Or Concrete Pipe</li> </ul>			
Features	<ul style="list-style-type: none"> <li>Ultra-portable</li> <li>Trace fiber-optic microducts 8mm ID and larger</li> </ul>	<ul style="list-style-type: none"> <li>Ultra-portable</li> <li>Short straight runs in pipe to 4" diameter</li> </ul>	<ul style="list-style-type: none"> <li>Tall handle &amp; wide wheel base for easy transport</li> <li>Trace longer sewer laterals</li> </ul>	<ul style="list-style-type: none"> <li>Stiffer rod with roller guide moves through corrugated and tile systems</li> </ul>	<ul style="list-style-type: none"> <li>Large frame carries longer lengths</li> <li>All-terrain wheels available</li> </ul>	<ul style="list-style-type: none"> <li>Stiffest rod for largest pipes &amp; longest runs</li> <li>All-terrain wheels available</li> </ul>
Lengths Available	100' - 300' (30.5 - 91.4m)		300' - 600' (91.4 - 183m)	300' - 400' (91.4 - 122m)	500' - 800' (152 - 244m) 1200' (366m)	300' - 1000' (91.4 - 305m)
Recommended Conduit	1/2" - 1" (15 - 25mm)	3/4" - 1-1/2" (20 - 40mm)	1" - 2" (25 - 50mm)	2" - 4" (50 - 100mm)		4" or larger (100mm)
Minimum Bend Radius	1.75" (4.5 cm)	2.5" (6.4 cm)	4" (10.2 cm)	6" (15 cm)		9" (23 cm)
Pull Strength	150 Lbs.	300 Lbs.	400 Lbs.	500 Lbs.		800 Lbs.
Accessory Kit	Included 15-18-AK		Included 16-14-AK	Included 12-516-AK		Included 13-716-AK
Dimensions	22" x 17" x 7" (55.9 x 43.2 x 17.8 cm)		36.25" x 24.0" x 13" (92.1 x 61 x 33 cm)	34.0" x 26.5" x 15.5" (86.4 x 67.3 x 39.4 cm)	40.0" x 32.0" x 18.0" (106 x 81.3 x 45.7 cm)	48" x 44" x 21" (121.9 x 111.8 x 53.3 cm)
Weight	11.1 - 15.0 lbs. (5.0 - 6.8 kg)	11.6 - 15.5 lbs. (5.3 - 7.0 kg)	28.0 - 39.0 lbs. (12.7 - 17.7 kg)	46.7 - 51.7 lbs. (21.2 - 23.5 kg)	65.0 - 105.0 (29.5 - 47.6 kg)	97.0 - 167.0 lbs. (44.0 - 75.8 kg)
Male End Ferrule Thread	1/4" - 20			3/8" - 16		

- Great bending strength
- All rodders include pulling eye or roller guide and repair kit
- All rodders (1/4" and larger) marked in 5' increments (1m metric marked available)

Scan QR code to learn more



07/2022