

## **Quick Link Connector**

The Quick Link Connector can be used in a variety of applications to connect a number of our products to each other. They provide low cost, ease of use, and no maintenance.



| Part No.  | Nominal Size | 2:1 Safe Working Load | Loop Inside Width | Overall Outside Length | Weight  |
|-----------|--------------|-----------------------|-------------------|------------------------|---------|
| 00660-187 | 3/16"        | 660 lb                | 1/2"              | 2"                     | 0.05 lb |
| 00660-250 | 1/4"         | 880 lb                | 1/2"              | 2-3/8"                 | 0.08 lb |
| 00660-312 | 5/16"        | 1,760 lb              | 5/8"              | 3"                     | 0.17 lb |
| 00660-375 | 3/8"         | 2,200 lb              | 11/16"            | 3-3/16"                | 0.23 lb |
| 00660-437 | 7/16"        | 2,600 lb              | 3/4"              | 3-1/2"                 | 0.31 lb |
| 00660-500 | 1/2"         | 3,300 lb              | 7/8"              | 4-1/8"                 | 0.51 lb |

## **Wire Rope Bridle Sling**

The purpose of this product is to allow multiple pulls at one time by attaching two, three, or four cables or ducts to the puller. The slings are manufactured from aircraft quality wire rope with thimble eyes for durability (tapered swages are also available). The various "legs" are staggered in length so the individual connections are not interfering with each other. The lead coupler can be easily dismantled to change out a leg or to add another leg.

Each leg is marked with load capacity and they have a three times safety factor on that rating. The safety factor is based on equal pull on all cables (horizontal pull only). Couplers and wire rope sling legs may be ordered separately. Other sling configurations are available upon request.

DUB-Lite (00503 series) or Line Swivels (00505 series) are recommended to permit free rotation of the bridle at the legs and coupler. The recommended swivels are sized to suit the load and connection: smaller swivels over the leg loop, a larger swivel to fit the shackle.

Note: 5 & 6-leg slings are available in 1/4" and 3/8" slings upon request.



|           |               |             | 3:1 Safe Working Load |                |         | Recommended DUB-Lite                             |  | Recommended Line Swivel                  |                                     |
|-----------|---------------|-------------|-----------------------|----------------|---------|--|--|--|-------------------------------------|
| Part No.  | Wire Diameter | No. of Legs | Leg Capacity          | Sling Capacity | Weight  | Over Shackle                                     | Over Leg Loop                                      | Over Shackle                             | Over Leg Loop                       |
| 23125-020 | 1/8"          | 2           | 650 lb                | 1,300 lb       | 0.5 lb  | 00503-202<br>00503-204<br>00503-205              | 00503-202  | 00505-020<br>00505-025<br>00505-027      | 00505-005<br>00505-010<br>00505-015 |
| 23125-030 | 1/8"          | 3           | 650 lb                | 1,950 lb       | 0.6 lb  |  |  |  |                                     |
| 23125-040 | 1/8"          | 4           | 650 lb                | 2,600 lb       | 0.6 lb  |  |  |  |                                     |
| 23250-020 | 1/4"          | 2           | 2,300 lb              | 4,600 lb       | 1.2 lb  | 00503-204<br>00503-205<br>00503-208<br>00503-210 | 00503-202  | 00505-027<br>00505-030                   | 00505-010<br>00505-015<br>00505-020 |
| 23250-030 | 1/4"          | 3           | 2,300 lb              | 6,900 lb       | 1.6 lb  |  |  |  |                                     |
| 23250-040 | 1/4"          | 4           | 2,300 lb              | 7,100 lb       | 2.0 lb  |  |  | 00505-035                                | 00505-025                           |
| 23375-020 | 3/8"          | 2           | 4,800 lb              | 9,600 lb       | 2.9 lb  | 00503-208*<br>00503-210*<br>00503-215            | 00503-204<br>00503-205<br>00503-208<br>00503-210   | 00505-035†                               | 00505-020                           |
| 23375-030 | 3/8"          | 3           | 4,800 lb              | 12,000 lb      | 3.7 lb  |  |  | 00505-040<br>00505-041                   | 00505-025<br>00505-027              |
| 23375-040 | 3/8"          | 4           | 4,800 lb              | 18,000 lb      | 5.9 lb  |  |  | 00505-045                                | 00505-030                           |
| 23500-020 | 1/2"          | 2           | 6,900 lb              | 13,800 lb      | 6.7 lb  | 00503-215  | 00503-204**<br>00503-205<br>00503-208<br>00503-210 | 0503-205 00505-041<br>0503-208 00505-045 | 00505-030<br>00505-035              |
| 23500-030 | 1/2"          | 3           | 6,900 lb              | 20,700 lb      | 8.6 lb  |  |  |  |                                     |
| 23500-040 | 1/2"          | 4           | 6,900 lb              | 28,300 lb      | 12.7 lb |  |  |  |                                     |

- \* These DUB-Lites do not fit the 23375-040.
- \*\* These DUB-Lites do not fit the 23500-040.
- † These Line Swivels do not fit the 23375-040.



