



## Making It Easier To Transport & Install Cable!

Designed by professional cable installers, J-Lift allows one person to load and unload cable reels quickly, safely and easily.

Directly mounts to service body pintle plate or easily slides into square hitch receiver with customer-supplied pintle hook mounting plate. The 1,000 lbs. lifting capacity\* easily handles:

Cable	Fiber
Strand	Wire
Conduit	Geothermal
Fence	<b>And More!</b>

Industry professionals have found the J-Lift makes their job easier **PLUS** saves time & money compared to using a trailer!

- Easy To Park & Back Up
- Parking Deck & Drive-Thru Accessible
- Reduced Fuel Usage
- Haul More Reels
- Lower Insurance Costs
- CDL Not Required
- Use On Multiple Trucks

- **One Person Operation**
- **Eliminates Need For Trailer**
- **1,000 Lbs. Lifting Capacity\***

\* Depending on vehicle tongue weight and hitch class rating







- One Person Operation
- Easily Lift & Transport Reels
- Eliminates Need For Trailer
- 1,000 Lbs. Lifting Capacity\*



**REMOTE CONTROL**

With the push of a button, one person can easily load and go in minutes. Corded J-Lift control is included; with optional wireless remote control available separately.

**DUAL ACTING HYDRAULICS**

Dual action and dual load-holding hydraulic pump and cylinders raise and lower with equal force - extremely convenient in cold climates and with lighter spools. This also allows faster stopping with a fully loaded reel for safer operation. **Exceptional RAISE, LOWER & STOP Capabilities!**

**POWDER COATED**

For long life performance and corrosion resistance.

**LIGHT KIT**

Connect to truck's 4-pin trailer output for brake lights and turn signals.



J-Lift Specifications	
Part Number	MTK-40
Dimensions	45" x 28" x 30"
Total Weight	293 Lbs.
Weight - Wiring	18 Lbs.
Power Source	12-Volt DC
Finish	Powder Coat
Hydraulic Pump	Dual Action with Corded Remote Control
Hydraulic Hoses	1/4" SAE, 5800 PSI
Cylinders	3000 PSI
Center Arbor	2.5" Diameter

Operating Specifications	
Maximum Reel Capacity	40" Wide x 48" Diameter Maximum
Maximum Lifting Capacity	1,000 Lbs.*
Hitch Required	Minimum Class IV Hitch
Hitch Recommended	Pintle Plate / Class V Hitch
Wiring Included	20', 4 AWG Harness With Jumper Clamps & Ring Terminal Options

\* Minimum Class IV hitch required. Reel weight plus 293 lbs. must not exceed vehicle tongue weight.

