

SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE, 8" (20.3cm) DIAMETER**
 Part Number: **9500-15EX, 9500-25EX**
 Style: **RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- -65°F to 250°F (-53°C to 121°C) temperature range
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs
- Meets requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end



AVAILABLE:

| Part No. | Diameter | Length | End-Straps |
|-----------|-------------|-------------|------------|
| 9500-15EX | 8" (20.3cm) | 15' (4.57m) | Dual |
| 9500-25EX | 8" (20.3cm) | 25' (7.62m) | Dual |

ACCESSORIES:

| Part No. | Ducting Size | Description |
|-----------|--------------|---|
| 9500-01 | 8" (20.3cm) | Duct to Duct Connector, with raised lip |
| 9500-35 | 8" (20.3cm) | Storage Rack for 8" (20.3cm) Ducting, up to 25' (7.62m) Ducting |
| 9500-45 | 8" (20.3cm) | Storage Bag |
| 9600-50EX | 8" (20.3cm) | Reducer, Statically conductive for 16" (40.6cm) blower |

SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE**
Part Number: **9550-15EX, 9550-25EX**
Style: **12" (30.4cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- Temperature resistant up to 250°F (121°C)
- Retractable, non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs
- Meet requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end



AVAILABLE:

| Part No | Diameter In (cm) | Length Ft (m) | End-Straps |
|-----------|---------------------|------------------|------------|
| 9550-15EX | 12" (30.4) | 15' (4.57) | Dual |
| 9550-25EX | 12" (30.4) | 25' (7.62) | Dual |

ACCESSORIES:

| Part No. | Ducting Size | Description |
|----------|--------------|---|
| 9550-01 | 12" (30.4) | Duct to duct connector with raised lip |
| 9600-36 | 12" (30.4) | Storage rack for 12" (30.4) ducting up to 25' (7.62m) ducting |
| 9600-45 | 12" (30.4) | Duct storage bag |

SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE, 16”(40.6cm) DIAMETER**
 Part Number: **9600-15EX, 9600-25EX**
 Style: **RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- Temp resistant up to -65°F to 250°F (-53°C to 121°C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Meet requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end



AVAILABLE:

| Part No. | Diameter In (cm) | Length Ft (m) | End-Straps |
|-----------|---------------------|------------------|------------|
| 9600-15EX | 16” (40.6) | 15’ (4.57) | Dual |
| 9600-25EX | 16” (40.6) | 25’ (7.62) | Dual |

ACCESSORIES:

| Part No. | Ducting Size In (cm) | Description |
|-----------|-------------------------|---|
| 9600-01 | 16” (40.6) | Duct to duct connector, with raised lip |
| 9600-36 | 16” (40.6) | Storage rack for 16” ducting, up to 25’ (7.62m) ducting |
| 9600-45 | 16” (40.6) | Duct storage bag |
| 9600-50EX | 8” (20.3) | Reducer, statically conductive for 16” (40.6m) blower to 8” (20.3m) ducting |

SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE, 20" DIAMETER**
 Part Number: **9650-15EX, 9650-25EX**
 Style: **RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- Temp resistant up to -65°F to 250°F (-53°C to 121°C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Meet requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end



AVAILABLE:

| Part No. | Diameter | Length | End-Straps |
|-----------|----------|---------|------------|
| 9650-15EX | 20" | 15 Feet | Dual |
| 9650-25EX | 20" | 25 Feet | Dual |

ACCESSORIES:

| Part No. | Ducting Size | Description |
|----------|--------------|---|
| 9650-01 | 20" | Duct to duct connector, with raised lip |
| 9600-45 | 20" | Duct storage bag |