

WORKS BARRICADE PLASTIC PANELS WITH GALVANIZED LEGS

TD2200 MODEL

**NCHRP350 CRASH TEST CERTIFIED
AND MEETS MUTCD STANDARDS**



FEATURES:

- **Type I and Type II Barricades can be purchased as assembled units or component parts. Legs and boards can be purchased separately. All barricade components are completely interchangeable.**
- **Legs are standard 45" manufactured using galvanized steel in 14 or 12 gauge thickness.**
- **Barricades are assembled utilizing 1/4-20 x 1" galvanized carriage bolts with high-bend mil spec split lock washers and nuts. Legs are hinged with two 1/2-13 X 1" hex nuts and 1/2-13 nylon locknuts.**
- **High impact plastic panels are reinforced to reduce bending and warping.**
- **Molded ribs provide protection to reflective sheeting.**

NCHRP350 Compliant: WZ-54
MASH Compliant Category I Device

All Sheeting Complies With
ASTM 4956 requirements.

COLORS AVAILABLE:

The TD2200 Works Barricades is currently available with White painted boards. Three D Traffic Works can manufacture this product to your desired color.

GENERAL INFORMATION:

General information is listed on the reverse side. The measurements provided are intended only as a source of information. They are given without guarantee and are not classified as a warranty. A specification will be sent to you upon request.



we got the works!!
Three D
TrafficWORKS
Innovative Traffic Safety Products



430 N. Varney Street. Burbank, CA. 91502 Tel: 877 843 9757 Fax: 818 841 5096
Email: sales@trafficwks.com Web: www.trafficwks.com



TD2200 MODEL

WORKS BARRICADE PLASTIC PANELS WITH STEEL LEGS

SPECIFICATIONS:

- **Folded Dimensions:**
Thickness: 1.81"
Length: 24"
Height: 45"
- **Plastic Board Material:**
UV Stabilized Polymer Alloy with a Cold Weather Protection Package. Meets EPA Recycled Content Guidelines: 95% Recycled Material.
- **Plastic Board Thickness: 0.63"**
- **Leg Material: 14 or 12 Gauge Galvanized Steel Roll Form.**
- **All sheeting complies with ASTM 4956.**

**NCHRP350 CRASH TEST CERTIFIED
 MEETS MUTCD STANDARDS
 MASH Compliant Category I Device**

