

Item	Parameter
<b>Description</b>	Single channel stethoscope
<b>Uses</b>	To aid cable identification particularly in situations where there are multiple cables
<b>Construction</b>	POM (Polyoxymethylene)
<b>Weight</b>	0.3lbs (0.125kg)
<b>Dimension</b>	1.5in(Dia.) x 2.2in(L) (39mm x 55mm)
<b>Features</b>	<ul style="list-style-type: none"> <li>- Ergonomic design</li> <li>- Auto recognition by Vivax-Metrotech receiver</li> </ul>
<b>Frequency Range</b>	512Hz to 32.8 kHz
<b>Compatible With Receiver</b>	vLocPro, vLocML, vLocDM, vLocPro2, vLocML2, vLocDM2, vLoc-9800
<b>External Connectors</b>	1 x 4 pin connector
<b>Approvals</b>	CE/FCC
<b>Temperature Range</b>	Operating : -4°F to 122°F (-20°C to 50°C) Storage : -40°F to 140°F (-40°C to 60°C)
<b>Weather Proof</b>	IP54
<b>Warranty</b>	12 months

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.



Toll-Free: 800-WCT-PROD (928-7763)  
 Local Phone: 310-822-5212  
 Fax: 310-306-9343  
 Email: info@wctproducts.com  
 Address: 13309 Beach Ave.  
 Marina del Rey, CA 90292  
 Website: www.wctproducts.com